


## ASSEMBLY INSTRUCTIONS



## Dot 13" Flush Mount

Item # PB 4000

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

### TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver

Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate **(B)** from fixture by removing screws **(D)**.
3. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)** using screwdriver **(E)**.
4. Connect fixture neutral wire (ribbed) to the driver neutral (marked "+") by pushing button and inserting wire.
5. Connect fixture hot wire (smooth with markings) to the driver hot (marked "-") by pushing button and inserting wire. (see diagram 1)
6. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 2). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.

**NOTE:** It is imperative that the fixture is grounded.

7. Connect driver neutral wire (ribbed) to the supply neutral wire (usually white) using wire nut **(A)**.
8. Connect driver hot wire (smooth with markings) to the supply hot wire (usually black) using wire nut **(A)**.

**CAUTION:** Do not reverse the hot and neutral connections.

9. Make sure all wire connections are tight, then carefully tuck into the junction box.
10. Install fixture to mounting plate **(B)** by securing with screws **(D)** using screwdriver **(E)** provided.

**Care Instructions:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.